Smart

Inclusions

Kitchen Appliances

- Fisher and Paykel 600mm Stainless Steel Cooker And 600mm Electric Oven
- Fisher and Paykel 600mm Slide Out Rangehood
- Provide Provision for Microwave

Benchtop and Cabinetry

- Laminated Kitchen Bench-top
- Melamine to Kitchen Under-Bench Cupboard and Overhead Cupboards
- Kitchen Sink Mixer Tap
- Splash-Back Tiles to Underside of Overhead Cupboards

Pantry and Fridge

- 4 Rows of Melamine Shelving for Walk in Pantry (when shown on plans)
- Fridge Provision with Space and Electrical Point and Storage Overhead

Electrical

- 2 Television Points
- 2 Telephone Points
- 15 LED Ceiling Down Lights
- LED Ceiling Light to Garage
- 2-way Switch on Staircase
- 20 Batten holders
- 1 Fan to Ensuite and Bathrooms
- Two (2) Smoke Detectors
- Earth Leakage Safety Switches to Meter Box
- Circuit Breakers to Meter Box

Bathroom & Ensuite

- 600mm Wall Hung White polyurethane vanity with slimline ceramic basin top
- Chrome Plug and Wastes to Outlets
- Chrome Single Lever Mixers to Vanities,
- Bathtub in Hub with Chrome Mixer
- Toilet Suite with Soft Close Action Seats
- 1 Hand Held Shower Head
- Frame-less Polished Edge Mirrors 600mm wide
- Framed Shower screen
- Chrome Double Towel Rails, Rings and Toilet Roll Holders

Wall Tiles

- Provide 1800mm tile height In En-suite & Bathrooms Showers
- Provide 1 height tile skirting to rest of the wall

Floor Coverings

- Provide tile flooring to Entry, lounge,
 Living, Kitchen, Walk-In-Pantry and Dining
- Provide Wall to Wall Quality Carpet to First Floor and Staircase- DHURSAN "Smart" Range

ALFRESCO

- Provide Sliding door to rear of Living/Dining
- Provide 1 gas and 1 Single Power Point
- Provide covered (Roof over) Alfresco with Recessed Ceiling

Laundry

- Quality Laundry Tub with PVC Cabinet and Sink Mixer
- Tiled Splash Back Above the Tub (1 tile height), one tile Skirting to Rest of Laundry Walls

DHURSAN CONSTRUCTION

Main Door Entrance

- Entrance door 920mm x 2060mm
 Sunburst hinged with Obscure glass
- Contemporary Handle with lock

Air Conditioning

 Provide Ducted Daikin Air Conditioning with 2 Zone and 2 Controller

Internal

- 2600mm Height to ground floor and 2450mm to first floor in lieu of standard
- Single Shelve with Hanging Rod to Walk in Robes

External

- Engineer Designed 'M' Class Concrete with waffle Pod Slab on Ground
- Engineered H2 Treated Timber Frame and Roof Trusses
- Face Brickwork Austral (wilderness) with off White Mortar and Weather Board
- Selected Roof tile
- Maintenance Free metal Facia and Gutter

Other Essentials

- BASIX Assessment and fees
- Fire retardant Sarking to Underside of Roof tiles
- Decorative Slimline Rainwater Tank (size to be determined as per BASIX)
- Ceiling Insulation R3.0
 - Wall Insulation R1.5
 1 Gas Bayonet Point to Living Area
- Six Star rated Cas Continuous flow Rheem hot Water System

Staircase and Staircase Balustrade

 Timber Handrail (Painted with Vertical metal Balustrade and MDF Treads and Risers (for Carpet)

Paint

 Taubman's three Coat Paint System to Walls and Two Coats to Ceilings

